



Roadie HD+35K

DC2K / 32,500 ANSI lumens

특장점	규격	옵션	이미지
밝기	32,500 ANSI lumens (35,000 Center lumens) ? 6.0kW Lamp 27,000 ANSI lumens (29,000 Center lumens) ? 4.5kW Lamp 18,000 ANSI lumens (19,500 Center lumens) ? 3.0kW Lamp 12,000 ANSI lumens (13,000 Center lumens) ? 2.0kW Lamp		
명암비	2000:1 (full on/off)		
Uniformity	90% brightness uniformity		
Display Type	3-chip 1.25" DMD		
실 해상도	DC2K (2048 x 1080)		
램프 종류	Xenon bubble (user-replaceable bulb)		
램프 수명	6.0kW 1000 hrs (750 hrs at 6.6kW) 4.5kW 900 hrs 3.0kW 2500 hrs 2.0kW 3500 hrs		
신호	HDTV formats VGA through to QXGA (2048 x 1536) Accepts all current HDTV/DTV formats Multi-standard video decoder Horizontal and vertical scaling, all inputs		
Pixel clock	210MHz		
Scan rates	Horizontal: 15kHz to 120kHz Vertical: 23.97Hz to 150Hz		
입력, 제어 및 네트워크	RGBHV/YPbPr: 5 BNC DVI-I Analog / Digital RGB/YPbPR (HDCP) S-video Composite video 2 RS-232 ports RS-422 ports GPIO port Ethernet (10/100) RJ45 with ChristieNET connectivity Built-in backlit LCD keypad Front and rear IR receivers 2 input slots for analog/digital modules		

기본 액세서리	Dual SD/HD-SDI input card Detached 7kW switching lamp ballast IR Remote keypad (with optional wired connection) Line cord 6ft ballast cable Handles for carrying and rigging User manual
옵션 액세서리	Input cards ? DVI, Dual SD/HD-SDI Christie Twist™ Remote IR sensor Wired remote control Rigging frame (required for portrait mode) Rigging clamps Lamp safety kit High-contrast aperture kits 6ft, 25ft, 50ft or 100ft ballast cable kit Service manuals KoRE 10-bit librarian software Filter replacement packs Portrait upgrade kit for existing Christie Roadie HD+35K models
Lens Mount Type	Tool-free lens insertion system Boresight adjustable
Motorized Lens Mount	Horizontal and vertical offset Focus Zoom
렌즈	0.8:1 Fixed Lens (offset: $\pm 45\%$ V, $\pm 15\%$ H) 1.1:1 Fixed Lens (offset: $\pm 74\%$ V, $\pm 21\%$ H) 1.25-1.45:1 Zoom Lens (offset: $\pm 100\%$ V, $\pm 35\%$ H) 1.45-1.8:1 Zoom Lens (offset: $\pm 53\%$ V, $\pm 17\%$ H) 1.8-2.4:1 Zoom Lens (offset: $\pm 53\%$ V, $\pm 17\%$ H) 2.2-3.0:1 Zoom Lens (offset: $\pm 53\%$ V, $\pm 17\%$ H) 3.0-4.3:1 Zoom Lens (offset: $\pm 53\%$ V, $\pm 17\%$ H) 4.3-6.0:1 Zoom Lens (offset: $\pm 53\%$ V, $\pm 17\%$ H) 5.5-8.5:1 Zoom Lens (offset: $\pm 100\%$ V, $\pm 35\%$ H)
프로젝터 전원 요구사항	Operating voltage: single phase 200-240 VAC @50/60Hz Max current: 3A max
발라스트 전원 요구사항	Type: detached 7kW switching lamp ballast Operating voltage: 3-phase 200-230 VAC @50/60Hz Max current: 24A per phase max Operating voltage: 3-phase 380-415 VAC @50/60Hz Max current: 16A per phase max
프로젝터 규격	(L x W x H): 53.6 x 31.5 x 22.8" (1362 x 800 x 577mm) Shipping dimensions (L x W x H): 65 x 41 x 35" (1650 x 1040 x 890mm) Weight 360lb (163kg) Shipping weight 460lb (209kg)
발라스트 규격	(L x W x H): 21 x 18 x 21" (533 x 457 x 533mm) Shipping dimensions (L x W x H): 28 x 25 x 31.5" (710 x 635 x 800mm) Weight 110lb (50kg) Shipping weight 145lb (66kg)
작동환경	Temperature: 5 to 35° C (40 to 95° F) Humidity: 20 ? 80% non-condensing
Regulatory	UL/CSA/IEC 60950 (3rd edition) FCC Class A, CE This product conforms to all relevant European directives, standards, safety, health and environmental concerns RoHS, WEEE