



HD6K-M

Full HD / 6,000 ANSI Lumens

특장점	규격	옵션	이미지	
밝기	Dual lamp: 6000 ANSI lumens (6300 center) lumens Single lamp: 3000 ANSI lumens (3300 center) lumens			
명암비	2500-10,000:1 using dynamic iris (full on, full off) 650:1 ANSI (typical)			
Uniformity	90% brightness uniformity			
Display type	3-chip 0.95" DLP			
실 해상도	HD (1920 x 1080) ~ QXGA(2,048x1,536)			
램프 종류	Dual 200W PVIP			
램프 수명	High power: 2000 hrs @ 200W Low power: 3000 hrs @ 150W			
기본 입력	Analog BNC Dual-link DVI			
옵션 입력	Analog BNC Dual-link DVI Dual SD/HD-SDI Video decoder Twin HDMI			
입력 신호	HDTV formats VGA through to QXGA (2048 x 1536) Accepts all current HDTV/DTV formats Multi-standard video decoder Horizontal and vertical scaling, all inputs			
Pixel clock	165 MHz			
Scan rates	Horizontal: 15 to 120 kHz Vertical: 23.97 to 150 Hz			
입력, 제어 및 네트워크	RS232 in/out RS422 in Ethernet (10/100) USB device GPIO (RS232 9-pin male connector) Built-in backlit LCD keypad Remote control (with optional wired XLR connection)			
광학 시스템	Dust sealed, 3-chip DMD light engine Motorized horizontal and vertical lens offset Scheimpflug (tilt) adjustment Built-in light shutter Tool-free lens insertion system			
고정 초점 렌즈	ILS lens 0.73:1 SX+/0.67:1 HD* ILS lens 1.2:1 SX+/1.1:1 HD			

줌 렌즈	ILS lens 1.25-1.6:1 SX+/1.16-1.49:1 HD** ILS lens 1.5-2.0:1 SX+/1.4-1.8:1 HD ILS lens 2.0-2.8:1 SX+/1.8-2.6:1 HD ILS lens 2.8-4.5:1 SX+/2.6-4.1:1 HD ILS lens 4.5-7.3:1 SX+/4.1-6.9:1 HD ILS lens 7.3-11.2:1 SX+/6.9-10.4:1 HD
Offsets	$\pm 100\%$ Vertical $\pm 50\%$ Horizontal (* $\pm 23\%V$ / $\pm 13\%H$) (** $\pm 70\%V$ / $\pm 45\%H$)
기본 액세서리	User manual IR remote Line cord
옵션 액세서리	Coarse dust filter Fog juice filter Ceiling mount Ceiling mount extension ILS lens adapter kit Stacking frame Christie AutoStack™ DMX512 interface card
주요 기능	LiteLOC™ Comprehensive Color Adjustment (CCA™) Embedded Christie Twist™ image warping and edge-blending Intelligent Lens System (ILS™) for zoom, focus, horizontal and vertical offset for all lenses Auto setup Digital keystone correction Dynamic iris Menus in five languages 99 channel memories Multi-windowing and processing (up to a 3 x 3 array) Motorized yellow notch filter (HD & WUXGA models only) Black level blending Built-in portrait display capabilities* 3D upgradable *Christie M Series stacking frame is required in portrait orientation
사용 전압	110-240 VAC 50/60 Hz
최대 동작 전류	13.2 A @ 100 VAC
전원	1320W
발열량	4508 BTU/hr
크기	(LxWxH): 22.1 x 19.7 x 10.2" (561 x 500 x 259mm)
무게	55 lbs (25kg)
작동환경	Temperature: 40 to 104° F (5 to 40° C) Humidity: 10-80% non-condensing
Regulatory approvals	UL/CSA/IEC 60,950 (3rd edition) FCC Class A, CE, CCC This product conforms to all relevant European directives, standards, safety, health and environmental concerns RoHS, WEEE