



Roadie 4K45

4K/45000 Center(43,000 ANSI) lumens

특장점	규격	옵션	이미지
밝기	45000 Center(43,000 ANSI) lumens		
명암비	2000:1 (full on/ full off)		
Display technology	3-chip 1.38" DMD		
실 해상도	4096 x 2160 Native 4K		
램프종류	7.0kW CDXL-70 6.0kW CDXL-60 4.5kW CDXL-30 3.0kW CDXL-20 2.0kW CDXL-20		
램프수명	7.0kW CDXL-70 - 400 hours 6.0kW CDXL-60 - 750 hours 4.5kW CDXL-30 - 900 hours 3.0kW CDXL-20 - 2,500 hours 2.0kW CDXL-20 - 3,500 hours		
Pixel clock	1.2Gpx/s - TrueLife Electronics		
입력	표준 2 x Dual 3G HD-SDI input card 2 x Twin display port input card 제어 및 네트워크 RS232 in Ethernet (10/100) RJ45 with ChristieNET connectivity Detachable control panel		
기본 액세서리	Ballast and cables User manual Wired TPC		
렌즈	Fixed 0.72:1 (no offset) 1.0:1 (Offset: Vertical: ± 29% Horizontal: 9%) Zoom 1.13-1.31:1 (Offset: Vertical: ± 56% Horizontal: 19%) 1.31-1.63:1 (Offset: Vertical: ± 13% Horizontal: 4%) 1.63-2.17:1 (Offset: Vertical: ± 13% Horizontal: 4%) 1.98-2.71:1 (Offset: Vertical: ± 13% Horizontal: 4%) 2.71-3.89:1 (Offset: Vertical: ± 13% Horizontal: 4%) 3.89-5.43:1 (Offset: Vertical: ± 13% Horizontal: 4%) 5.43:1 -7.69:1 (Offset: Vertical: ± 56% Horizontal: 19%)		
크기,무게	Dimensions (L x W x H) Head : 1329(L) x 647(W) x 522(H) mm Ballast : 542(L) x 445(W) x 532(H) mm Weight Head : 129 kg Ballast : 57 kg		
작동환경	Temperature: 10 to 35°C (50 to 95°F) Humidity: 0 to 90% non-condensing		
전원요구사항	소비전압 Head : 200V Ballast : 3-phase 200-230 VAC @50/60Hz / 380-415 VAC @50/60Hz 소비전류 Head : 7A Ballast : 38A per phase max / 26A per phase max		
Regulatory	(EC) No. 1907/2006 (REACH) CAN/CSA C22.2 No. 60950-1 UL 60950-1 IEC 60950-1 EN 60950-1 FCC, Part 15, Subpart B, Class A EN55022/CISPR22 Class A EN55024/CISPR24		