



HD14K-M

Full HD / 12,000 ANSI Lumens

특장점	규격	옵션	이미지	
밝기	Dual lamp: 12,000 ANSI lumens (13,500 center) lumens Single lamp: 6,000 ANSI lumens (6,750 center) lumens			
명암비	2500-10,000:1 (full on/off) 650:1 ANSI (typical)			
Uniformity	90% brightness uniformity			
Display type	3-chip 0.95" DLP			
실 해상도	Full HD (1920 x 1080) ~ QXGA(2,048x1,536)			
램프 종류	Dual 450W NSH			
램프 수명	High power: 1,250 hrs @ 450W Low power: 1,500 hrs @ 360W			
기본 입력	Analog (5 BNC) Dual-link DVI			
옵션 입력	Analog (5 BNC) Dual-link DVI Dual 3G SD/HD-SDI Video decoder Twin HDMI			
입력 신호	HDTV formats VGA through to QXGA (2048 x 1536) Accepts all current HDTV/DTV formats Multistandard video decoder Horizontal and vertical scaling, all inputs			
Pixel clock	165 MHz			
Scan rates	Horizontal: 15 to 120 kHz Vertical: 23.97 to 150 Hz			
입력, 제어 및 네트워크	RS232 in/out RS422 in Ethernet (10/100) USB device GPIO (RS232 9-pin male connector) Built-in backlit LCD keypad Remote control (with optional wired XLR connection)			
광학 시스템	Dust-sealed, 3-chip, DMD light engine Motorized horizontal and vertical lens offset Scheimpflug (tilt) adjustment Built-in light shutter Tool-free lens insertion system			

고정 초점 렌즈	ILS lens 0.73:1 SX+/-0.67:1 HD* ILS lens 1.2:1 SX+/-1.1:1HD
줌 렌즈	ILS lens 1.25-1.6:1 SX+/-1.16-1.49:1 HD** ILS lens 1.5-2.0:1 SX+/-1.4-1.8:1 HD ILS lens 2.0-2.8:1 SX+/-1.8-2.6:1 HD ILS lens 2.8-4.5:1 SX+/-2.6-4.1:1 HD ILS lens 4.5-7.3:1 SX+/-4.1-6.9:1 HD ILS lens 7.5-11.2:1 SX+/-6.9-10.4:1 HD
Offsets	+/- 120% Vertical +/- 42% Horizontal (* ±35%V / ±12%H) (** ±102%V / ±40%H)
기본 액세서리	IR remote Line cord
옵션 액세서리	Coarse dust filter Fog juice filter Ceiling mount Ceiling mount extension ILS lens adapter kit Stacking frame Christie AutoStack™ DMX512 interface card
주요 기능	LiteLOC™ Comprehensive Color Adjustment (CCA™) Embedded Christie Twist image warping and edge-blending Intelligent Lens System (ILS) for zoom, focus, horizontal and vertical offset for all lenses Auto setup Digital keystone correction Menus in five languages 99 channel memories Multiwindowing and processing (up to a 3 x 3 array) Motorized yellow notch filter (HD and WUXGA models only) Black-level blending 24/7 operation Built-in portrait display capabilities 3D upgradable
사용 전압	110-240 VAC 50/60 Hz
최대 동작 전류	15A @ 100 VAC
전원	1500W
발열량	5118 BTU/hr
크기	(LxWxH): 22.1 x 19.7 x 10.2" (561 x 500 x 259mm)
무게	55lbs (25kg)
작동환경	Temp: 40 to 104° F (5 to 40° C) Humidity: 20-80% non-condensing
Regulatory approvals	Directives (EC) 2002/95/EC (RoHS); 2002/96/EC (WEEE); Regulation (EC) No. 1907/2006 (REACH) CAN/CSA C22.2 No. 60950-1 UL 60950-1 IEC 60950-1 FCC, Part 15, Subpart B, Class A EN55022/CISPR22 Class A EN55024 / CISPR24 Certifications marks (check with Christie for latest update): cULus (Canada & US), CE (EU), CCC (China), GoST-R (Russia), KC (Korea), PSE (Japan), C-Tick (Australia & New Zealand), South Africa