



D4K2560

4K / 22,500 ANSI lumens

밝기	22,500 ANSI lumens
명암비	2000:1 contrast ratio
Display type	3-chip 1.38" DMD
실 해상도	Native 4K (4096 x 2160)
램프 종류	22,500 ANSI [25,000 center] lumens - 3.0kW CDXL-30SD lamp 16,000 ANSI [18,000 center] lumens - 3.0kW CDXL-30 lamp 9,000 ANSI [10,000 center] lumens - 2.0kW CDXL-20 lamp
램프 수명	3.0kW CDXL-30SD - 1,500 hours 3.0kW CDXL-30 - 2,500 hours 2.0kW CDXL-20 - 3,500 hours
입력 신호	2x Dual 3G HD-SDI input card 2x Twin display port input card
입력 신호	Accepts 4K (4096x2160) and Quad HD (3840x2160) ?4 x DisplayPort 1.1a ?4K/Quad HD - 24 to 60Hz 4:4:4 8-/10-bit ?4K/Quad HD - 24 to 60Hz 4:2:2 8-/10-/12-bit ?2 x DisplayPort 1.1a ?4K/Quad HD - 24 to 60Hz 4:4:4 8-/10-bit ?4 x HD SDI ?4K/Quad HD - 24 to 30Hz 4:4:4 12-bit (4 x 3G HD-SDI) ?4K/Quad HD - 24 to 30Hz 4:2:2 12-bit (4 x 3G HD-SDI) ?4K/Quad HD - 24 to 30Hz 4:2:2 10-bit (4 x HD-SDI) ?4K/Quad HD - 50 to 60Hz 4:2:2 10-bit (4 x 3G HD-SDI) ?4 x DVI ?4K/Quad HD - 24 to 60Hz RGB 8-bit ?2 x DVI (Dual Link) ?4K/Quad HD - 24 to 60Hz RGB 8-bit
입력, 제어 및 네트워크	RS-232 Ethernet (10/100) RJ45 with ChristieNET™ connectivity Detachable LCD control module
Lens mount Type	Tool-free lens insertion system Boresight adjustable Motorized horizontal and vertical lens offset Motorized zoom and focus adjustment
고정 초점 렌즈	0.72:1 (no offset) 1.0:1 (Offset: Vertical: ± 29% Horizontal: 9%)

줌 렌즈	1.13-1.31:1 (Offset: Vertical: $\pm$ 56% Horizontal: 19%) 1.31-1.63:1 (Offset: Vertical: $\pm$ 13% Horizontal: 4%) 1.63-2.17:1 (Offset: Vertical: $\pm$ 13% Horizontal: 4%) 1.98-2.71:1 (Offset: Vertical: $\pm$ 13% Horizontal: 4%) 2.71-3.89:1 (Offset: Vertical: $\pm$ 13% Horizontal: 4%) 3.89-5.43:1 (Offset: Vertical: $\pm$ 13% Horizontal: 4%) 5.0 -7.69:1 (Offset: Vertical: $\pm$ 56% Horizontal: 19%)
기본 액세서리	Detachable LCD control module AC line cord for projector head CDXL-30SD lamp
옵션 액세서리	CDXL-20 lamp CDXL-30 lamp Heat extraction fan kit (required when operating the projector) Rack mount pedestal Replacement air filter for the light engine Replacement air filter for the liquid cooling radiator Lamp adapter kit for CDXL-20 Christie Twist 4K
전원 요구사항	Operating voltage: Single phase 200-240 VAC @50/60Hz Operating current: 23A max at 200V
크기	(LxWxH): 51.1 x 25.5 x 19.0" (1298 x 648 x 483mm)
무게	273lbs (124kg)
작동환경	Operating temperature: 50-95°F (10-35°C) Humidity (noncondensing): 20-80%
Regulatory approvals	This product conforms to these regulations related to product safety, environmental requirements and electromagnetic compatibility (EMC): Directives: ?(EC) 2011/65/EU (RoHS) ?2012/19/EU (WEEE) Regulations: ?(EC) No. 1907/2006 (REACH) ?CAN/CSA C22.2 No. 60950-1 ?UL 60950-1 ?IEC 60950-1 ?EN 60950-1 ?FCC, Part 15, Subpart B, Class A ?EN55022/CISPR22 Class A ?EN55024/CISPR24 The product is designed to comply to the rules and regulations required for the product to be sold in various regional markets, including: USA/Canada, EU, Norway, Australia/New Zealand, Kuwait, China, Korea, Japan, Mexico, Ukraine, Russia, South Africa, and Saudi Arabia.