



D4K3560

4K / 32,500 ANSI lumens

특장점	규격	옵션	이미지	
밝기	32,500 ANSI lumens			
명암비	2000:1 contrast ratio			
Display type	3-chip 1.38" DMD			
실 해상도	Native 4K (4096 x 2160)			
램프 종류	32,500 ANSI [35,000 center] lumens - 6.0 kW lamp 27,000 ANSI [29,000 center] lumens - 4.5 kW lamp 18,000 ANSI [19,500 center] lumens - 3.0 kW lamp 12,000 ANSI [13,000 center] lumens - 2.0 kW lamp			
램프 수명	Xenon bubble, user-replaceable bulb1 6.0kW - 750 hours 4.5kW - 900 hours 3.0kW - 2,500 hours 2.0kW - 3,500 hours			
입력 신호	2x Dual 3G HD-SDI input card 2x Twin display port input card			
입력 신호	Accepts 4K (4096x2160) and Quad HD (3840x2160) ?4 x DisplayPort 1.1a ?4K/Quad HD - 24 to 60Hz 4:4:4 8-/10-bit ?4K/Quad HD - 24 to 60Hz 4:2:2 8-/10-/12-bit ?2 x DisplayPort 1.1a ?4K/Quad HD - 24 to 60Hz 4:4:4 8-/10-bit ?4 x HD SDI ?4K/Quad HD - 24 to 30Hz 4:4:4 12-bit (4 x 3G HD-SDI) ?4K/Quad HD - 24 to 30Hz 4:2:2 12-bit (4 x 3G HD-SDI) ?4K/Quad HD - 24 to 30Hz 4:2:2 10-bit (4 x HD-SDI) ?4K/Quad HD - 50 to 60Hz 4:2:2 10-bit (4 x 3G HD-SDI) ?4 x DVI ?4K/Quad HD - 24 to 60Hz RGB 8-bit ?2 x DVI (Dual Link) ?4K/Quad HD - 24 to 60Hz RGB 8-bit			
입력, 제어 및 네트워크	RS-232 Ethernet (10/100) RJ45 with ChristieNETTM connectivity Detachable LCD control module			
Lens mount Type	Tool-free lens insertion system Boresight adjustable			
Lens mount Motorized	Horizontal and vertical offset Focus Zoom			
고정 초점 렌즈	0.72:1 (no offset) 1.0:1 (Offset: Vertical: $\pm$ 29% Horizontal: 9%)			

기본 액세서리	Detachable LCD control module AC line cord for projector head Detached 7kW low-ripple switch mode lamp ballast (required to operate projector) CDXL-60 lamp
옵션 액세서리	?CDXL-20 lamp ?CDXL-30 lamp ?CDXL-45 lamp ?Heat extraction fan kit (required when operating the projector) ?Rack mount pedestal ?Replacement air filter for the light engine ?Replacement air filter for the liquid cooling radiator ?Lamp adapter kit for CDXL-20 ?Christie Twist 4K (limited to 30 frames per second)
전원 요구사항	?Operating voltage: Single phase 200-240 VAC @50/60Hz ?Operating current: 27A max at 200V
발라스트 전원 요구사항	?Type: detached, 7kW low-ripple, switch-mode lamp ballast ?Operating voltage: 3-phase 200-230 VAC @ 50/60Hz ?Operating current: 38A per phase max ?Operating voltage: 3-phase 380-415 VAC @ 50/60Hz ?Operating current: 26A per phase max
크기	Projector head (LxWxH): 51.1 x 25.5 x 19.0" (1298 x 648 x 483mm) Ballast (LxWxH): 21 x 18 x 21" (533 x 457 x 533mm)
무게	Projector head 251lbs (114kg) Ballast 89lbs (40.5kg)
작동환경	Operating temperature: 50-95°F (10-35°C) Humidity (noncondensing): 20-80%
Regulatory approvals	This product conforms to these regulations related to product safety, environmental requirements and electromagnetic compatibility (EMC): Directives: ?(EC) 2011/65/EU (RoHS) ?2012/19/EU (WEEE) Regulations: ?(EC) No. 1907/2006 (REACH) ?CAN/CSA C22.2 No. 60950-1 ?UL 60950-1 ?IEC 60950-1 ?EN 60950-1 ?FCC, Part 15, Subpart B, Class A ?EN55022/CISPR22 Class A ?EN55024/CISPR24 The product is designed to comply to the rules and regulations required for the product to be sold in various regional markets, including: USA/Canada, EU, Norway, Australia/New Zealand, Kuwait, China, Korea, Japan, Mexico, Ukraine, Russia, South Africa, and Saudi Arabia.